

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 July 2003 (17.07.2003)


PCT

(10) International Publication Number  
WO 03/058591 A1

- (51) International Patent Classification<sup>7</sup>: G09G 3/28
- (21) International Application Number: PCT/IB02/05598
- (22) International Filing Date:  
23 December 2002 (23.12.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
102 00 827.2 11 January 2002 (11.01.2002) DE
- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Stein-damm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, SI, US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VAN DER BROECK, Heinz [DE/DE]; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (74) Agent: VOLMER, Georg; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD OF CONTROLLING A CIRCUIT ARRANGEMENT FOR THE AC POWER SUPPLY OF A PLASMA DISPLAY PANEL



(57) Abstract: A method of controlling a circuit arrangement for an AC voltage supply of a plasma display panel, the circuit arrangement comprising at least a transistor bridge constituted by the bridge transistors (T1, T2, T3, T4), an input voltage (U0), a capacitor (Cp) of the plasma cell and a charging circuit comprising an auxiliary voltage (Uh), a first auxiliary transistor (T11) and a first coil (L1) and at the beginning of the charging operation the first auxiliary transistor (T11) is turned on, characterized in that once the first auxiliary transistor (T11) has been turned on, the second bridge transistor (T2) of the half bridge continues to be turned on for a delay time tv and is turned off after the delay time tv has elapsed.

WO 03/058591 A1